

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. **(Currently Amended)** An image signal processing apparatus for use as a preprocessing apparatus for an image display apparatus that displays images in accordance with color image signals, comprising:

an image signal receiving means for receiving a color image signal; and

a chromaticity adjustment means for performing a gamma correction on calculation using
signal values of the received color image signal, performing a calculation using
the signal values on which the gamma correction was performed, and adjusting
the chromaticity of an image to be displayed by the image display apparatus for
each of primary colors red, green, and blue, separately.
2. **(Original)** The image signal processing apparatus of Claim 1, wherein the chromaticity adjustment means includes:

a matrix operation means for multiplying the signal values of the received color image
signal with a determinant;

a parameter receiving means for receiving a predetermined parameter; and

a determinant changing means for changing the determinant in accordance with the
received parameter, wherein

the chromaticity adjustment means adjusts the chromaticity for each primary color by
performing a calculation using the changed determinant.
3. **(Cancelled)**
4. **(Original)** The image signal processing apparatus of Claim 3, wherein

gradation conversion characteristics in the gamma correction means are substantially
equal to gradation conversion characteristics required to correct gradation
reproduction characteristics of a display device of the image display apparatus.

5. **(Original)** The image signal processing apparatus of Claim 3 further comprising
an inverse gamma correction means for performing an inverse gamma correction on the
color image signal output from the chromaticity adjustment means.

6. **(Original)** The image signal processing apparatus of Claim 1, wherein
the received color image signal is a YUV signal,
the image signal receiving means includes
a signal conversion means for converting the received YUV signal into an RGB signal,
and
the chromaticity adjustment means adjusts the chromaticity for each primary color by
performing a calculation on signal values of the RGB signal.

7. **(Currently Amended)** An image display apparatus, comprising:
an image signal preprocessing means for preprocessing a color image signal; and
an image display means for displaying images in accordance with the preprocessed color
image signal, wherein
the image signal preprocessing means includes
an image signal receiving means for receiving the color image signal, and
a chromaticity adjustment means for performing a gamma correction on
calculation using signal values of the received color image signal,
performing a calculation using the signal values on which the gamma
correction was performed, and adjusting the chromaticity of an image to
be displayed by the image display apparatus for each of primary colors
red, green, and blue, separately.

8. **(Original)** The image display apparatus of Claim 7, wherein the chromaticity adjustment means includes:
- a matrix operation means for multiplying the signal values of the received color image signal with a determinant;
 - a parameter receiving means for receiving a predetermined parameter; and
 - a determinant changing means for changing the determinant in accordance with the received parameter, wherein
- the chromaticity adjustment means adjusts the chromaticity for each primary color by performing a calculation using the changed determinant.
9. **(Cancelled)**
10. **(Original)** The image display apparatus of Claim 9, wherein
- gradation conversion characteristics in the gamma correction means are substantially equal to gradation conversion characteristics required to correct gradation reproduction characteristics of a display device of the image display apparatus.
11. **(Original)** The image display apparatus of Claim 7, wherein
- the received color image signal is a YUV signal,
 - the image signal receiving means includes
 - a signal conversion means for converting the received YUV signal into an RGB signal,
 - and
 - the chromaticity adjustment means adjusts the chromaticity for each primary color by performing a calculation on signal values of the RGB signal.

12. **(Currently Amended)** A multidisplay apparatus for allowing a plurality of image display units to display a plurality of images side by side on a screen, comprising:
 an image distribution means for generating, from a received color image signal, a plurality of color image signals for a plurality of images to be displayed respectively by the plurality of image display units; and
 a plurality of chromaticity adjustment means which respectively correspond to the plurality of image display units and each perform a calculation using signal values of one of the plurality of color image signals to be input to a corresponding image display unit and adjust the chromaticity to a target chromaticity level for each of the primary colors red, green, and blue of an image to be displayed by the corresponding image display unit for each of primary colors red, green, and blue, separately, wherein
the target chromaticity level for each primary color is set to a value in chromaticity coordinates that is among coordinate values belonging to a common chromaticity range which is common to ranges of chromaticity that can be displayed by the plurality of image display units, and is closest to a standard chromaticity coordinate value for each primary color.
13. **(Original)** The multidisplay apparatus of Claim 12, wherein the chromaticity adjustment means includes:
 a matrix operation means for multiplying the signal values of the received color image signal with a determinant;
 a parameter receiving means for receiving a predetermined parameter; and
 a determinant changing means for changing the determinant in accordance with the received parameter, wherein
 the chromaticity adjustment means adjusts the chromaticity for each primary color by performing a calculation using the changed determinant.

14. **(Original)** The multidisplay apparatus of Claim 12, wherein the chromaticity adjustment means includes
- a gamma correction means for performing a gamma correction on the color image signal,
- and
- the chromaticity adjustment means performs a calculation using signal values of the color image signal on which the gamma correction was performed.
15. **(Original)** The multidisplay apparatus of Claim 14, wherein
- gradation conversion characteristics in the gamma correction means are substantially equal to gradation conversion characteristics required to correct gradation reproduction characteristics of a display device of the image display apparatus.
16. **(Original)** The multidisplay apparatus of Claim 14 further comprising
- an inverse gamma correction means for performing an inverse gamma correction on the color image signal output from the chromaticity adjustment means.
17. **(Original)** The multidisplay apparatus of Claim 12, wherein
- the received color image signal is a YUV signal,
- the image signal receiving means includes
- a signal conversion means for converting the received YUV signal into an RGB signal,
- and
- the chromaticity adjustment means adjusts the chromaticity for each primary color by performing a calculation on signal values of the RGB signal.
18. **(Currently Amended)** A chromaticity adjustment method for adjusting the chromaticity of images displayed by a multidisplay apparatus that allows a plurality of image display units to display a plurality of images side by side on a screen, the multidisplay apparatus including a plurality of chromaticity adjustment means which respectively correspond to the plurality of image display units and each receive a parameter, perform a calculation

using signal values of a color image signal in accordance with the received parameter, and adjust the chromaticity of an image to be displayed by a corresponding image display unit for each of primary colors red, green, and blue, separately, the chromaticity adjustment method comprising:

a first step for inputting an image signal to each image display unit for each of primary colors red, green, and blue, allowing each image display unit to display an image, and measuring the chromaticity and the brightness of the image displayed by each image display unit for each primary color; and

a second step for determining, in accordance with measured values of the chromaticity and the brightness, the parameters to be respectively input to the plurality of chromaticity adjustment means so that chromaticity values of the images displayed by the plurality of image display units are substantially equal to each other for each primary color, wherein

the second step includes:

a first sub-step for obtaining, from chromaticity values for each primary color, ranges of chromaticity that can be displayed by the plurality of image display units;

a second sub-step for obtaining a common chromaticity range which is common to the obtained ranges of chromaticity, and setting target chromaticity values for each of red, green, and blue out of values belonging to the common chromaticity range; and

a third sub-step for determining the parameters so that chromaticity values of the images displayed by the plurality of image display units are substantially equal to the target chromaticity values for each of red, green, and blue.

19. (Cancelled)